





MRH 125




Mast - Reactions

5.2 ft - P 41A					
Height (ft)	98	115	131	148	164
Height (ft)	124.3	113.5	107.9	102.4	97.1
10.9 ft	1	0	1	2	0
16.4 ft	6	6	5	4	5
F2 (Ust)	● 136	133	133	134	133
	■ 158	152	159	166	167
F3 (Ust)	● 102	100	100	96	101
	■ 124	118	126	132	134


5.2 ft - S 41A - 					
Height (ft)	98	115	131	148	164
Height (ft)	129.3	123.7	112.9	102	96.5
10.9 ft	2	0	2	1	2
16.4 ft	5	6	4	4	3
F1 (Ust)	● 89	90	89	89	87
	■ 95	96	95	93	94






 Motorized accesses of Cab-IN and TCL types: Adapted mast compositions, base ballast and reactions.

Note: When "ASCE" is noted in this data sheet it is referring to 115 mph Wind Zone, Exposure B, Design Wind Speed = 98 mph. See back cover for design wind speed calculations.

6.6 ft - P 602B						
Span (ft)	98	115	131	148	164	
r_s (ft)	206.4	200.8	195.5	190	184.4	
Height (ft)	10.9	1	2	0	1	2
	16.4	11	10	11	10	9
F2 (Ust)	● 158	160	157	160	157	
	■ 332	337	339	343	346	
F3 (Ust)	● 117	114	113	116	117	
	■ 291	296	299	303	306	



6.6 ft - V 60A - 						
Span (ft)	98	115	131	148	164	
r_s (ft)	176.5	165.7	160.1	149.3	143.7	
Height (ft)	10.9	0	2	0	2	0
	16.4	9	7	8	6	7
F1 (Ust)	● 99	100	99	99	95	
	■ 133	129	130	126	126	





Anchorage



Base ballast

 (USt) / 5.2 ft - S 41A - 

ft	98	115	131	148	164
129.3	125.7				
123.7	119.1	125.7			
112.9	112.4	119.1	125.7		
102	99.2	112.4	119.1	125.7	
96.5	99.2	105.8	112.4	119.1	125.7
80.1	86	92.6	99.2	105.8	112.4
63.7	72.8	79.4	86	92.6	99.2
47.2	59.5	66.1	72.8	79.4	86

 (USt) / 6.6 ft - V 60A - 

ft	98	115	131	148	164
176.5	145.5				
165.7	132.3	145.5			
160.1	119.1	132.3	145.5		
149.3	92.6	119.1	132.3	145.5	
143.7	92.6	105.8	119.1	132.3	145.5
127.3	79.4	79.4	92.6	105.8	119.1
110.9	66.1	79.4	79.4	79.4	92.6
94.5	52.9	66.1	66.1	79.4	79.4
78.1	52.9	52.9	52.9	66.1	66.1
61.7	39.7	39.7	52.9	52.9	52.9
45.3	39.7	39.7	39.7	39.7	52.9

Load curves



ft	56	66	72	82	89	98	98.9	105	115	115.2	121	131	131.4	138	148	ft
148	8.8	8.8	8.6	7.1	6.3	5.3	-	4.8	4.2	-	3.8	3.2	-	2.9	2.5	USt
131	8.8	8.8	8.6	7.1	6.3	5.3	-	4.8	4.2	-	3.8	3.3	3.3	USt		
115	8.8	8.8	8.8	7.6	6.8	5.7	-	5.2	4.4	4.4	USt					
98	8.8	8.8	8.8	7.3	6.5	5.6	5.5	USt								

 =  - 0.16 USt max.




ft	56	66	72	82	89	98	98.9	105	115	115.2	121	131	131.4	138	148	154	164	ft
164	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.1	3.6	-	3.2	2.8	2.55	2.2	USt
148	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4	3.5	-	3.2	2.75	USt		
131	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.1	3.5	3.5	USt				
115	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	USt							
98	4.4	4.4	4.4	4.4	4.4	4.4	4.4	USt										


Jib weight & counter-jib ballast

Height (ft)	Jib Weight (lb) (+/- 5%)		Counter-jib Ballast (lb)	Total Weight (lb)
	②	⑧		
164 ft	12,887	-	4	41,888
148 ft	12,215	12,612	4	41,888
131 ft	11,432	11,829	4	41,888
115 ft	10,561	10,958	4	41,888
98 ft	9,514	9,911	4	41,888

CCL - 10,472 lb


















Luffing jib











Dimensions and weight

Slewing crane part:  164 ft -  33 LVF




Slewing crane part		L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Counter-jib	 H 33 LVF 50 LVF	19.3	12.9	11.6	12,721 13,735
	 H 33 LVF 50 LVF	19	7.4	8.2	11,707 12,721
Cab	 H V140 SR	15.9	7.8	8.2	3,748
Towerhead	 H 5.2 ft 6.6 ft	7.1 7.6	6.8 7.8	7.7 7.7	10,362 12,710
Jib section	 H ①	20.5	6.8	8.4	13,007
	 H ②	17.2	5.2	8.3	2,172
	 H ③	33.6	4.7	8.2	3,208
	 H ④	33.5	4.7	7.8	3,296
	 H ⑤	17	4.7	6.4	1,047
	 H ⑥	16.9	4.6	6.3	871
	 H ⑦	16.9	4.5	6.3	783
	 H ⑧	16.9	4.5	6.3	672
Pulley block	 H W → L	4.8	1.2	4.9	838
	 H L	4.8	0.7	4.1	441
Hoisting winch (+ rope)	 H L W	7.7 8.2	5 5	5.3 5.3	3,428 4,442

Crane tower		L (ft)	W (ft)	H (ft)	lb (+/- 5%)	
T41 T61		5.2 ft 6.6 ft	35.6 35.5	12.3 13.6	13.5 14.7	15,653 21,385
K 447B K 447E KM 447E KM 449E K 649B KM 649E		5.2 ft 5.2 ft 5.2 ft 5.2 ft 6.6 ft 6.6 ft	33.5 33.5 33.5 33.5 33.6 33.8	5.5 5.3 5.3 5.3 6.8 6.7	5.3 5.3 5.3 5.3 6.7 6.7	7,606 7,474 7,088 8,448 11,663 10,692
K 447A KMT 447A K 449A KMT 449A KR 649A KRMT 649A K 649A KMT 649A		5.2 ft 5.2 ft 5.2 ft 5.2 ft 6.6 ft 6.6 ft 6.6 ft 6.6 ft	17.1 17.1 17.1 17.1 17.2 17.2 17.2 17.2	5.5 5.5 5.5 5.5 6.9 6.9 6.8 6.8	5.3 5.3 5.3 5.3 6.8 6.8 6.7 6.7	4,079 3,847 4,916 4,696 7,165 6,724 6,184 5,666
K 447C K 649C KRMT 649C		5.2 ft 6.6 ft 6.6 ft	11.3 11.7 11.7	5.5 6.8 6.9	5.3 6.7 6.8	2,998 4,376 5,401
Fixing angles		P 41A P 602B	1.2 2.1	1.2 2.1	3.7 4.2	293 650
Basic mast unit		S 41A V 60A	11.9 16.4	6.4 7.9	6.8 7.9	6,537 9,674
Struts		S 41A V 60A	10.4 14.8	0.9 1	0.8 1	489 919
Half-bearer		S 41A V 60A	16.7 22	2 2.3	5.8 7.6	2,524 3,519


Mechanisms

480 V - 60 Hz											hp	kW	
	33 LVF 20 Optima	fpm	85	112	164	233	43	56	82	116	33	22	1539 ft
		USt	4.4	3.3	2.2	1.1	8.8	6.6	4.4	2.2			
	50 LVF 20 Optima	fpm	144	190	269	387	72	95	135	194	50	37	2287 ft
		USt	4.4	3.3	2.2	1.1	8.8	6.6	4.4	2.2			
	40 VVH 80	min	2							40	30		
	RVF 152 Optima +	rpm	0 → 0.8							2 x 5.5	2 x 4		

33 LVF 20 Optima



50 LVF 20 Optima



	IEC 60204-32		kVA
	480 V (+6% -10%) 60 Hz		33 LVF : 74 → 61 kVA 50 LVF : 88 kVA

These mast combinations meet the EN 14439 and ASME B30.3-2016 specifications for "out of service" wind conditions, provided the illustrated wind speed matches required design wind speed for the location of the tower crane. The "out of service" design wind speed was determined in accordance with ASCE 7-10, Figure 26.5-1A. The wind velocity, used for this configuration was 98 mph (158 kph), which represents a nominal design 3-second wind gust at 33 ft (10 m) above ground for Exposure B category. A factor of 0.85 was applied to the 700-year ultimate design wind speed of 115 mph (185 kph), per ASCE 37-02, with the assumption that this crane is considered a temporary structure used during a construction period of 2 years or less.

- Standard equipment
- Weathering position
- Required power
- Options
- Lorry 44 ft
- Power Control Function: winch speeds adapted to the available power
- Reactions in service
- Container High Cube 40 ft, and/or Flat Rack 20 ft
- Reactions out of service
- Hoisting
- Consult us
- Jib weight
- Luffing
- Total ballast weight
- Slewing
- Jib articulation axis
- Travelling

This commercial document is not legally binding. For any technical information, please refer to the corresponding instructions.

